

Claim Amendments

1. (canceled)

2. (canceled)

3. (canceled)

4. (currently amended) ~~The transceiver front-end of claim 3, further comprising~~ A transceiver front-end comprising:

a first feed point, configured for connecting to a first antenna, for conveying communication signals in a first frequency band in a first signal path via the first antenna;

a second feed point, configured for connecting to a second antenna electrically separated from the first antenna, for conveying communication signals in a second frequency band in a second signal path, wherein the second frequency band is at least partially overlapped with the first frequency band, wherein the first frequency band substantially covers a frequency range of 1850 MHz to 1910 MHz, and the second frequency band substantially covers a frequency range of 1805 MHz to 1880 MHz;

a first module, operatively connected to the first feed point, for disposing the first signal path for transmitting the communication signals, and

a second module, operatively connected to the second feed point, for disposing the second signal path for receiving the communication signals.

5. (original) The transceiver front-end of claim 4, wherein the second module further comprises a third signal path for reception in a third frequency band different from the second frequency band.

6. (original) The transceiver front-end of claim 5, wherein the third frequency band substantially covers a frequency range between 2110 MHz and 2170 MHz.

7. (original) The transceiver front-end of claim 6, wherein the communication signals in the first and second frequency bands are transmitted in a GSM mode, and the communication signals in the third frequency band are transmitted in a W-CDMA mode.

8. (original) The transceiver front-end of claim 7, wherein the second module further comprises a fourth signal path for transmission substantially in a frequency range of 1920 MHz to 1980 MHz in a W-CDMA mode.

9. (original) The transceiver front-end of claim 8, wherein the first module further comprises a fifth signal path for reception substantially in a frequency range of 1930 MHz to 1990 MHz.

10. (currently amended) The transceiver front-end of claim [[1]] 4, wherein the first frequency band also substantially covers a ~~first~~ further frequency range of 1710 MHz to 1785 MHz for transmission, ~~and a second frequency range of 1850 MHz to 1910 MHz for transmission, and the second frequency band substantially covers a third frequency range of 1805 MHz to 1880 MHz for reception.~~

11. (currently amended) The transceiver front-end of claim 10, wherein the first signal path comprises:

- a first end;
- a second end operatively connected to the first feed point;
- a first passband filter disposed between the first end and the second end for filtering the communication signals in the first frequency range;
- a second passband filter disposed in parallel to the first passband filter between the first end and the second end for filtering the communication signals in the ~~second~~ further frequency range;
- a first matching circuit operatively connected to the first end; and
- a second matching circuit operatively connected to the second end.

12. (original) The transceiver front-end of claim 10, wherein the first feed point is also connected to a third signal path for receiving communication signals substantially in a frequency range of 1930 MHz to 1990 MHz.

13. (original) The transceiver front-end of claim 12, wherein a switching circuit operatively connected to first feed point for providing a switching function between the first signal path and the third signal path.

14. (previously presented) The transceiver front-end of claim 13, wherein the switching circuit comprises

- a first PIN diode connected in series to the first signal path,
- a second PIN diode connected to the third signal path in a shunt configuration, and
- a phase shifting circuit connected between the first and second PIN diodes.

15. (previously presented) The transceiver front-end of claim 13, wherein the switching circuit comprises:

- a first solid state switch connected in series to the first signal path, and
- a second solid state switch connected in series to the third signal path.

16. (original) The transceiver front-end of claim 12, wherein the communications signals received in the third signal path are transmitted in a GSM mode.

17. (original) The transceiver front-end of claim 16, wherein the first feed point is further connected to signal paths for transmission and reception of communication signals in a GSM mode operating in a frequency range lower than 1000 MHz.

18. (currently amended) The transceiver front-end of claim ~~[[1]]~~ 4, wherein

~~the first frequency band substantially covers a frequency range of 1805 MHz to 1880 MHz for transmitting the communication signals, and~~

~~the second frequency band substantially covers a frequency range of 1850 MHz to 1910 MHz for receiving the communication signals, and wherein~~

the ~~second~~ first feed point is also connected to a third signal path for reception of communication signals substantially in a frequency range of 1930 - 1990 MHz.

19. (currently amended) The transceiver front-end of claim ~~[[1]]~~ 4, wherein

~~the first frequency band substantially covers a frequency range of 1805 MHz to 1880 MHz for transmitting the communication signals, and~~

~~the second frequency band substantially covers a frequency range of 1850 MHz to 1910 MHz for receiving the communication signals, and wherein~~

the first feed point is also connected to a third signal path for transmission of communication signals substantially in a frequency range of the 1920 MHz – 1980 MHz.

20. (currently amended) The transceiver front-end of claim 18, wherein the ~~first~~ second feed point is also connected to a fourth signal path for transmission of communication signals substantially in a frequency range of the 1920 MHz – 1980 MHz.

21. (currently amended) The transceiver front-end of claim 20, wherein the ~~first~~ second frequency band also covers a further frequency range substantially between 1710 MHz to 1785 MHz.

22. (currently amended) The transceiver front-end of claim 21, wherein the ~~second~~ first feed point is also connected to a fifth signal path for reception of communication signals in a frequency range substantially between 2110 MHz and 2170 MHz.

23. (currently amended) The transceiver front-end of claim 22, wherein the ~~first~~ second feed point is also connected to further signal paths for transmission and reception of communication signals in a GSM mode operating in a frequency range lower than 1000MHz.

24. (currently amended) The transceiver front-end of claim 22, ~~wherein the portable communication device further comprises a third antenna, said transceiver front-end further comprising a third module having a third feed point operatively connected to [[the]] a third~~

antenna, the third feed point electrically separated from the first and second feed point, wherein the third module further comprises

at least one further signal path for receiving a communication signal substantially in one of the frequency ranges: (1805 - 1880 MHz), (1930 - 1990 MHz), and (2110 - 2170 MHz).

25. (canceled)

26. (canceled)

27. (currently amended) A method for use in communications, comprising:

operatively connecting a first signal path to a first feed point for conveying communication signals in a first frequency band via a first antenna, and

operatively connecting a second signal path to a second feed point for conveying communication signals in a second frequency band, wherein the first frequency band is at least partially overlapped with the second frequency band ~~The method of claim 25~~, wherein the first frequency band substantially covers a frequency range of 1850 MHz to 1910 MHz for transmission of the communication signals, and the second frequency band substantially covers a frequency range of 1805 MHz to 1880 MHz for reception of the communication signals.

28. (currently amended) The method of claim ~~[[25]]~~ 27, ~~wherein the first frequency band substantially covers a frequency range of 1850 MHz to 1910 MHz for transmission of the communication signals, and the second frequency band substantially covers a frequency range of 1805 MHz to 1880 MHz for reception of the communication signals, and wherein the reception is also carried out in a third signal path in a frequency range substantially between 2110 MHz and 2170 MHz~~, said method further comprising:

operatively connecting the third signal path to the second feed point.

29. (previously presented) The method of claim 28, wherein the transmission is also carried out in a fourth signal path in a frequency range substantially between 1930 MHz and 1990 MHz, said method further comprising:

operatively connecting the fourth signal path to the first feed point.

30. (currently amended) The method of claim ~~[[25]]~~ 27, ~~wherein the first frequency band substantially covers a frequency range of 1850 MHz to 1910 MHz for transmission of the communication signals, and the second frequency band substantially covers a frequency range of 1805 MHz to 1880 MHz for reception of the communication signals, and~~ wherein the reception is also carried out in a third signal path in a frequency range substantially between 2110 MHz and 2170 MHz, said method further comprising:

operatively connecting the third signal path to the first feed point.

31. (previously presented) The method of claim 30, wherein the transmission is also carried out in a fourth signal path in a frequency range substantially between 1930 MHz and 1990 MHz, said method further comprising:

operatively connecting the fourth signal path to the second feed point.

32. (currently amended) A communication device, comprising:

a first RF antenna;

a second RF antenna electrically separated from the first antenna; and

a transceiver front-end having a plurality of signal paths for conveying communication signals in the communication device, including at least a first signal path for conveying a communication signal in a first frequency band, and a second signal path for conveying a communication signal in a second frequency band, which is at least partially overlapped with the first frequency band, wherein the front-end further comprises:

a first feed point, operatively connected to the first antenna, for conveying the communication signals in the first signal path in the communication device via the first antenna;  
[[and]]

a second feed point, operatively connected to the second antenna, for conveying the communication signals in the second signal path in the communication device via the second antenna so that the communication signals in the partially overlapped frequency bands are conveyed via different antennas; [[,]]

a first module, operatively connected to the first feed point, for disposing the first signal path; and

a second module, operatively connected to the second feed point, for disposing the second signal path, and wherein the first frequency band substantially covers a frequency range of 1805 MHz to 1880 MHz, and

the second frequency band substantially covers a frequency range of 1850 MHz to 1910 MHz.

33. (canceled)

34. (canceled)

35. (canceled)

36. (original) The communication device of claim 32, comprising a mobile phone.

37. (original) The communication device of claim 32, comprising a communicator device.

38. (currently amended) A transceiver front-end module, comprising:

means, configured to be connected to a first antenna in a communication device, for conveying communication signals in a first frequency band in a first signal path via the first antenna; ~~and~~

means, configured to be connected to a second antenna in the communication device, for conveying communication signals in a second frequency band in a second signal path, wherein the first antenna is electrically separated from the second antenna and the second frequency band is at least partially overlapped with the first frequency band and wherein the communication signals in the second frequency are configured to be conveyed in the second signal path via the second antenna so that the communication signals in the partially overlapped frequency bands are conveyed via different antennas;

means, disposed in the first signal path, for filtering the communication signals in the first frequency range; and

means, disposed in the second signal path, for filtering the communication signals in the second frequency range, wherein

the first frequency band substantially covers a frequency range of 1805 MHz to 1880  
MHz, and  
the second frequency band substantially covers a frequency range of 1850 MHz to 1910  
MHz.

39. (canceled)